Dual-Winding Flat-Wire Output Inductor

Product Design Reference | PMT-PR-2026-1112-15 | Rev A/0 | 2026-11-12

This reference reproduces published product information and its stated evidence status. Final project specifications require an approved drawing and sample acceptance record.

Application and Validation

Two windings, 4.0 µH ±10% each (1 kHz / 0.3 V), 5 turns of 1.0 × 3.0 mm flat wire per winding. 40.5 × 26.0 × 18.5 mm max, 4-pin through-hole on PPS base. −40 to +125 °C. Hipot core–coil AC 500 V / 60 s, IR ≥ 100 MΩ @ DC 500 V. RoHS.

Published values are provided for application review. Design values, simulation results, rendered images and measured values retain the status stated above. Final specifications and acceptance criteria require an approved drawing and project-specific sample testing.

Please provide topology, voltage, RMS and peak current, switching frequency, cooling, insulation requirements and available mounting space.

Project Review and Contact

Send voltage, topology, frequency, RMS and peak current, loaded inductance or turns ratio, thermal boundary, insulation and available mounting dimensions. Sample fees and delivery schedule are confirmed in the project quotation.

3rd Floor, Building 1, No. 22 Dongda Road, Dongkeng Community, Fenghuang Street, Guangming District, Shenzhen, Guangdong 518132, China

Phone: +86 13537658938 | Email: zyong@promagtech.cn | www.promagtech.com

Product page: https://www.promagtech.com/products/dual-winding-output-inductor.html

© SHENZHEN PROMAGTECH CO., LTD | www.promagtech.com | zyong@promagtech.cn | +86 13537658938